

Application

Designed for low mounting heights for interior and exterior locations, the unshielded luminaire has a directing and guiding lighting effect. The illuminance level on the lit surface is lower, but the ambient brightness is greater with increased vertical illuminance.

Materials

Luminaire housing constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Faceplate constructed of 316 grade machined stainless steel
White safety glass
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	3.4 W
System wattage	4.9 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	50 lumens (3000K)
Lifetime at Ta = 25° C	50,000 h (L70)

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3 (EXPRESS)**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel.
Custom colors are not available.
Stainless steel requires regular cleaning and maintenance, much like household appliances to maintain its luster and prevent tarnishing or the appearance of rust like stains.

Type:

BEGA Product:


Project:

Modified:

Available Accessories

19535 Concrete protection cover

See individual accessory spec sheet for details.



LED recessed wall · unshielded				
	LED	A	B	C
22 130	ADA 3.4 W	7 1/2	3 1/8	4

