

Application

Designed for low mounting heights for interior and exterior locations. LED recessed wall luminaires with shielded light are ideal for glare-free illumination of ground surfaces, building entrances, stairs, and footpaths.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Clear safety glass with optical texture
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners
 Stainless steel screw clamps
 Painted aluminum installation housing

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP65
 Weight: 0.6lbs

Electrical

Operating voltage 24V DC (remote power supply req.)
 LED module wattage 2.1 W
 System wattage 3.0W
 Color rendering index Ra > 80
 Luminaire lumens 8 lumens (3000K)
 Lifetime at Ta = 25° C 50,000 h (L70)

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3 (EXPRESS)**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:

BEGA Product:


Project:

Modified:

Available Accessories

- 19580** Remote 25W LED driver and box
- 19591** Remote 50W LED driver and box

See individual accessory spec sheet for details.



LED recessed wall · shielded				
	LED	A	B	C
22203	ADA 2.1 W	3 1/8	3 1/8	4

