

Application

Designed for low mounting heights for interior and exterior locations, the shielded light distribution is ideal for the glare-free illumination of ground surfaces, building entrances, stairs, and footpaths.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
White safety glass
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 2.2 lbs

Electrical

Operating voltage 120-277V AC
Minimum start temperature -30°C
LED module wattage 3.9W
System wattage 6.0W
Controllability 0-10V dimmable
Color rendering index $R_a > 90$
Luminaire lumens 159 lumens (3000K)
Lifetime at $T_a = 15^{\circ}\text{C}$ $> 500,000$ h (L70)
Lifetime at $T_a = 45^{\circ}\text{C}$ 172,000 h (L70)

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3 (EXPRESS)**
2700K - Product number + **K27**
Amber - Product number + **AMB**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors Black (BLK) White (WHT) RAL:
 Bronze (BRZ) Silver (SLV) CUS :



LED recessed wall · shielded				
	LED	A	B	C
22 272	ADA 3.9W	5 7⁄8	5 7⁄8	4 1⁄8

Type:
BEGA Product:
Project:
Modified:

