

Application

Designed for low mounting heights for interior and exterior locations, the wide spread light distribution is suitable for illuminating corridors and pathways.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
Clear safety glass with optical texture
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 2.2lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30°C
LED module wattage	3.9W
System wattage	6.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	253 lumens (3000K)
Lifetime at Ta = 15°C	>500,000 h (L70)
Lifetime at Ta = 45°C	172,000 h (L70)

LED color temperature


4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3 (EXPRESS)**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



LED recessed wall · wide spread				
	LED	A	B	C
22377	ADA 3.9W	5 7⁄8	5 7⁄8	4 1⁄8

Type:
BEGA Product:
Project:
Modified:

