

**Application**

This LED wall luminaire with a wide spread light distribution can be used to illuminate ground surfaces along walls. Can be used for uplight or downlight applications.

**Materials**

Luminaire housing constructed of die-cast marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
 Clear safety glass  
 Reflector made of pure anodized aluminum  
 Silicone applied robotically to casting, plasma treated for increased adhesion  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65  
 Weight: 6.8 lbs

**Electrical**

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	15.8 W
System wattage	21 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	2187 lumens (3000K)
LED service life (L70)	60,000 hours

**LED color temperature**

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**
- Amber - Product number + **AMB**

**Wildlife friendly amber LED - Optional**

Luminaire is optionally available with a narrow bandwidth, amber LED source (585-600nm) approved by the FWC. This light output is suggested for use within close proximity to sea turtle nesting and hatching habitats. Electrical and control information may vary from standard luminaire.


LED module wattage	29.4 W (Amber)
System wattage	34.6 W (Amber)
Luminaire lumens	851 lumens (Amber)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :



**LED wall luminaire · wide spread light distribution**

	LED	A	B	C
<b>22383</b>	15.8 W	9 1/2	4 1/8	7 7/8

Type:  
 BEGA Product:  
 Project:  
 Modified:

