


# BEGA



Photometric Filename: 23259.IES


TEST: BE\_23259  
 TEST LAB: BEGA  
 DATE: 2/21/2018  
 LUMINAIRE: 23 259  
 LAMP: 19.5W LED

**Characteristics**


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2169
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	94
Total Luminaire Watts	23
Ballast Factor	1.00
CIE Type	General Diffuse
Spacing Criterion (0-180)	N.A.
Spacing Criterion (90-270)	N.A.
Spacing Criterion (Diagonal)	N.A.
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.23 ft (Diameter)
Luminous Height	2.26 ft

**Zonal Lumen Summary**

Zone	Lumens
0-10	1.15
10-20	11.94
20-30	37.40
30-40	74.54
40-50	118.06
50-60	162.24
60-70	201.56
70-80	231.11
80-90	246.58
90-100	246.58
100-110	231.11
110-120	201.56
120-130	162.24
130-140	118.06
140-150	74.54
150-160	37.40
160-170	11.94
170-180	1.15



Wall mount fixture - isofootcandle grid on floor  
 Mounting height = 5 ft. Grid spacing = 10 ft.



Wall mount fixture - isofootcandle grid on wall  
 Grid spacing = 5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.