

**Application**  
This LED wall washer luminaire has light output in one direction. This luminaire is ideally suited for the even illumination of vertical mounting surfaces. Arranged individually or in groups, they are a great design element for a host of lighting applications. For downlight applications only.


**Materials**  
Luminaire housing constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Clear safety glass  
Reflector made of pure anodized aluminum  
Silicone applied robotically to casting, plasma treated for increased adhesion  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners  
**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 64  
Weight: 2.9lbs

**Electrical**  
Operating voltage 120-277V AC  
Minimum start temperature -20° C  
LED module wattage 8.4 W  
System wattage 10 W  
Controllability 0-10V dimmable  
Color rendering index Ra > 80  
Luminaire lumens 421 lumens (3000K)  
Lifetime at Ta = 15° C >500,000 h (L70)  
Lifetime at Ta = 45° C 181,000 h (L70)

**LED color temperature**  
4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.  
Available colors    Black (BLK)    White (WHT)    RAL:  
                             Bronze (BRZ)    Silver (SLV)    CUS:



LED wall luminaire · light output on one side				
	LED	A	B	C
24 370	8.2 W	4 3⁄4	5 1⁄8	5 1⁄2

Type:  
BEGA Product:  
Project:  
Modified:

