


BEGA

Photometric Filename: 33503.ies

TEST: BE_33503
TEST LAB: BEGA
DATE: 9/26/2017
LUMINAIRE: 33 503
LAMP: 4.7W LED




Characteristics


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	417
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	60
Total Luminaire Watts	7
Ballast Factor	1.00
CIE Type	Semi-Direct
Spacing Criterion (0-180)	1.30
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.42
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.62 ft (Diameter)
Luminous Height	0.08 ft

Zonal Lumen Summary

Zone	Lumens
0-10	11.23
10-20	32.27
20-30	49.32
30-40	60.36
40-50	63.97
50-60	59.65
60-70	48.07
70-80	31.67
80-90	17.34
90-100	11.49
100-110	10.79
110-120	9.37
120-130	6.54
130-140	3.64
140-150	1.26
150-160	0.10
160-170	0.03
170-180	0.02



Ceiling Mount Fixture - Isofootcandle Grid on Floor
Mounting Height = 10 ft. Grid Spacing = 5 ft.



Wall Mount Fixture - Isofootcandle Grid on Floor
Mounting Height = 5 ft. Grid Spacing =

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

4/4/2018