

Application

The material thickness and strong crystal glass makes this impact-resistant LED luminaire extremely robust. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials

Luminaire housing constructed of die-cast marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Heavy pressed crystal glass, inside white
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 1.3lbs

Electrical

Operating voltage	24V DC (remote power supply req.)
LED module wattage	0.95 W
System wattage	3 W
Color rendering index	Ra > 90
Luminaire lumens	85 lumens (3000K)
Lifetime at Ta = 15° C	50,000 h (L70)

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :

Type:

BEGA Product:

Project:

Modified:

Available Accessories

19591 Remote 50W LED driver and box
19580 Remote 25W LED driver and box

See individual accessory spec sheet for details.



LED wall luminaire · shielded				
	LED	A	B	Required wiring box
33506 ADA	0.95 W 24V DC	4	3 1/8	19538