

Application

The material thickness and strong crystal glass makes this impact-resistant LED luminaire extremely robust. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials

Luminaire housing constructed of die-cast marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy  
Heavy pressed crystal glass, inside white  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65  
Weight: 3.1 lbs

Electrical

|                           |                    |
|---------------------------|--------------------|
| Operating voltage         | 120-277VAC         |
| Minimum start temperature | -30° C             |
| LED module wattage        | 2.8 W              |
| System wattage            | 6.6 W              |
| Controllability           | 0-10V dimmable     |
| Color rendering index     | Ra > 90            |
| Luminaire lumens          | 243 lumens (3000K) |
| Lifetime at Ta = 15° C    | 50,000 h (L70)     |

LED color temperature

4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3 (EXPRESS)**  
2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

|                  |              |              |       |
|------------------|--------------|--------------|-------|
| Available colors | Black (BLK)  | White (WHT)  | RAL:  |
|                  | Bronze (BRZ) | Silver (SLV) | CUS : |

Type:  
BEGA Product:  
Project:  
Modified:



| LED wall luminaire · shielded |           |       |   |
|-------------------------------|-----------|-------|---|
|                               | LED       | A     | B |
| 33507                         | ADA 2.8 W | 6 1/4 | 4 |

