

**Application**

Designed to provide down lighting effects for interior and exterior locations featuring narrow beam light distribution.

**Materials**

Luminaire housing constructed of die-cast marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy

Clear safety glass

Reflector made of pure anodized aluminum

Silicone applied robotically to casting, plasma treated for increased adhesion

High temperature silicone gasket

Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations

Protection class IP 64

Weight: 1.5 lbs

**Electrical**

Operating voltage 120-277V AC

Minimum start temperature  $-40^{\circ}\text{C}$

LED module wattage 1.9W

System wattage 3.0W

Controllability 0-10V dimmable

Color rendering index  $Ra > 80$

Luminaire lumens 158 lumens (3000K)

LED service life (L70) 60,000 hours

**LED color temperature**

4000K - Product number + **K4 (EXPRESS)**

3500K - Product number + **K35**

3000K - Product number + **K3 (EXPRESS)**

2700K - Product number + **K27**

Amber - Product number + **AMB**

**Wildlife friendly amber LED - Optional**

Luminaire is optionally available with a narrow bandwidth, amber LED source (585-600nm) approved by the FWC. This light output is suggested for use within close proximity to sea turtle nesting and hatching habitats. Electrical and control information may vary from standard luminaire.

LED module wattage 2.1 W (Amber)

System wattage 5.3W (Amber)

Luminaire lumens 57 lumens (Amber)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

**Wall luminaire with light in downward direction**

	LED	$\beta$	A	B	C
<b>33 579</b> <b>ADA</b>	1.9 W	23 °	3	5 1/8	3 3/4

$\beta$  = Beam angle

**BEGA** 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com  
© copyright BEGA 2018 Updated 03/20/19

